

*EXTRA CARE MUST BE TAKEN WHEN USING MURIATION

*EXTREMELY IMPORTANT TO VENTILATE THE WALK-IN

ACID OR OTHER HARSH CLEANING MATERIALS.

PROPERLY WHILE CONCRETE IS CURING.

CARROLL COOLERS MUST KNOW IF YOU ARE USING

QUARRY TILE IN THE WALK-IN OR BUTTING UP TO

THE WALK-IN. ROUGH OPENINGS FOR PASS THRU

DOORS AND CCI DOORS WILL NEED MODIFICATION TO

ALLOW THE DOORS TO OPEN AND CLOSE PROPERLY.

CORE MATERIAL

20

400

R15578

FLAME SPREAD

SMOKE DEVELOPED

STEEL

20

OVER 500

<u>ALUMINUM</u>

30

OVER 500

PORTION OR ALL OF THIS WALK-IN IS TO BE

CARROLL COOLERS, INC. SALES DEPT. IMMEDIATELY

INSTALLED IN A DEPRESSION, CONTACT THE

1-800-764-6834

P.0. AY 30 WEST; A 51401 764-6834 3-6748 HIGHWAY LL, IOWA E 19705 HIGI CARROLL, I PHONE (80 FAX (712)

8 ω, ရှို့မျှန်မျှ ≅∞`

ALL NECESSARY REVISIONS MUST BE NOTED

ON THIS DRAWING. FINAL DRAWING WILL BE

PRODUCED USING A SIGNED APPROVAL DWG.

WALK-IN COMPLIES WITH ALL PROVISIONS OF SECTION 312 OF THE ENERGY INDEPENDENCE AND SECURITY ACT OF 2007