



NEW PRO3 TOP MOUNT, SELF-CONTAINED, LOW TEMP SYSTEM 208-230 VOLT, 3 PHASE

A)-(1) surplus Heatcraft mnfg, PRO3 top-mount, self-contained low temp packaged refrigeration system

Unit mod: PTN052L6CE, mnfg'ed 2020

208-230 volt, 3 phase, r-404a

Units are designed for indoor use, fully assembled with no piping or loose components to install. Units are also precharged with r-404a and include electronic control of freezer temperature.

Approx. dim: 42" w x 52" l x 19" h, approx. net wgt: 270 lbs

Operating range: 0 to -20 degree freezer temp, +80 to +110 degree ambient

\$4,500. Per surplus unit, fob oshkosh, wi.

Amperage-voltage data

12.2 amps 3/208/230v mca for unit

15.0 amps 3/208/230v mopd for unit

Ambient temp: 80 degrees

Box temp: 0 -10 -20

Ratings: 8400 6430 4690

Ambient temp: 90 degrees

Box temp: 0 -10 -20

Ratings: 7470 5720 4170

Ambient temp: 95 degrees

Box temp: 0 -10 -20

Ratings: 7000 5360 3910

Ambient temp: 100 degrees

Box temp: 0 -10 -20

Ratings: 6440 4930 3600

Ambient temp: 110 degrees

Box temp: 0 -10 -20

Ratings: 5410 4140 3020